

PICOTE SUPER MIDI MILLER

Strong Yet Flexible



The Super Midi Miller is designed for cleaning, descaling, root removal, and cutting/reinstatements in DN70-150 (3-6") pipes. It has a range of 20m (65') that can be increased by an additional 10m (32') with a shaft extension. It can also be paired with the Picote Maxi Coating Pump to coat pipes DN70-200 (3-8").

The Super Midi sits squarely between the Mini and Maxi Miller capabilities, offering the added strength of the larger 12mm (1/2") shaft, a flexible outer shaft casing, and a weight of only 69kg (152 lbs). It is fed by a standard wall outlet making it very easy to use on almost any jobsite*.

USES AND BENEFITS

- Plugs into a standard wall outlet making it very easy to use on almost any jobsite*.
- The Super Midi's more flexible outer shaft casing makes it easy to navigate through multiple bends.
- High Speed/High Torque: 500-1500 rpm.
- Standard safety features include: protective outer shaft casing, operator presence foot control, electronic safety clutch, internal GFI, and an emergency stop to help keep you and your equipment investment protected.

* Use with a 110V / 16 Amp transformer in UK.

Technical Specifications

Category	Measurement
Pipe Size Ranges	
Cleaning / Descaling	DN70-150 (3-6")
Cutting / Reinstatement	DN70-150 (3-6")
Picote Brush Coating™	DN70-200 (3-8")
Usable Shaft Length	20m (65')
Shaft Extensions	10m (32')
Shaft Size	12mm (1/2")
Casing Type	Regular
Output Power	1.5kW
Speed	500-1500 RPM
Power	UK/US: 110/120V, 15 Amp
	EU: 220/230V, 16 Amp
Weight	69kg (152 lbs)
Size	1122 x 712 x 466mm
	45 x 28 x 18"
Safety Features	Protective outer shaft casing, operator presence foot control, electric safety clutch, & emergency stop.
IP Class	54

More Info/Guides/Technical Support:

- Visit picoteinstitute.com for e-learning courses, educational videos, quick guides, & manuals.
- For more information on products, spare parts, assembly and operation, consult the Super Midi Miller Manual or contact Picote Technical Support.
- For hands-on product training, Picote operates training centers in USA, UK, and Finland.

PRODUCTS AND SPARE PARTS

Products and Parts	
Part Number	Description
3551031220	Super Midi 12/20
3551031220US	Super Midi 12/20 110v US
3551031220UK	Super Midi 12/20 110v UK
Parts & Accessories	
1312020125022	Super Midi Replacement Shaft 12mm (½") 22m (72')
9330012000	Regular Outer Casing for 8mm (½") Shaft
9550000034	Strain Relief Midi Miller/Super Midi
1350000020	Picote Flexible Shaft Lubricant Bottle (0.5 litres/17oz)
1350000021	Picote Flexible Shaft Lubricant Package (6 bottles)