

## PICOTE XPRESS COATING SYSTEM

### *Superior Trenchless Pipe Rehabilitation*



The Xpress Brush Coating System provides a revolutionary solution for rehabilitation of 1¼ to 12" (DN32-300) pipes, boasting rapid curing times, zero waste, and quick setup providing unmatched savings in both cost and time.

The heart of the system is the innovative Xpress Coating Pump featuring dual hydraulic resin cylinders for the new 1:1, 100% solids, single color epoxy. It has a built-in extended life battery and internal resin heater ensuring several hours of working time and optimized resin temperature (with the added flexibility of being usable while charging, providing limitless time on the jobsite).

The system also includes a motorized Delivery Hose Reel with 131 feet (40m) of delivery hose allowing for easier setup, movement and storage.

## USES AND BENEFITS

- **Picote Xpress 1:1 Ratio Epoxy:**

Applied in ≈1mm thickness per coat & curing time as low as 1 hour\* per coat resulting in minimal number of coats needed, little time between coats, and quick return to service.

- Single color (light grey), 100% Solids Epoxy with Zero VOCs.
- As little as **1 hour curing time** between coats (@77°F/25°C).
- **Superior thickness of ≈ 1mm** per layer (@77°F/25°C).
- Bucketed resin containers **reduce waste & costs**.
- \*Optional Picote Heater speeds up curing times.

- **Motorized Return Reel with quick connect/multi use hoses:**

- Hoses are capped & ready for immediate re-use.
- Eliminates consumables waste and setup time.
- Almost instantaneous setup for subsequent coats.

- **Internal Resin Heater** on pump runs off the battery to maintain resin temperature during transport and usage.

- **Reel Heating Blanket** maintains hose reel resin temperature. Heating Blanket can run off Xpress Pump battery or be plugged in.

- Vertical design, tri-wheel stair climbers, and 32' (10m) corded remote allows easy transport on stairs and hard to reach places.

- **Go Small!** Included hose package for ¼-2" (DN32-50) pipes up to 50' (15m) in length.

- Use in conjunction with Picote Millers & Coating Brushes.

### Technical Specifications

Category	Specification
Cylinder Capacity	Pump: .26 gal (1 litre)
	Filler: .71 gal (2.7 litres)
Weight (empty)	Pump: 100kg (220 lbs)
	Reel: 50kg (110 lbs)
Size (WxLxH)	Pump: 26.9x58.1x25.7" (683x1476x653mm)
	Reel: 23.3x27.6x28.9" (592x701x734mm)
Battery	Internal (24V, 882Wh)
Resin	1:1 / 100% Solids





More Info/Guides/Technical Support:

- Visit [picoteinstitute.com](http://picoteinstitute.com) for e-learning courses, educational videos, quick guides, & manuals.
- For more information on spare parts, assembly and operation, consult the Picote Operation & Safety Manual or contact Picote Technical Support.
- For product training, Picote operates training centers in USA, UK & Finland.

PRODUCTS & PARTS

Product & Parts	
PN	Description
2220300000	Xpress Coating System
2220300000U	Xpress Coating System UK
2220300000US	Xpress Coating System US
2220300004	Xpress Reel Heating Blanket EU
2220300004U	Xpress Reel Heating Blanket UK
2220300004US	Xpress Reel Heating Blanket US
2220300005B	Picote Xpress Epoxy Base US (2.94 gal /30.8 lbs)
2220300005C	Picote Xpress Epoxy Catalyst US (2.94 gal / 24.15 lbs)
2220300003B	Picote Xpress Epoxy Base EU/UK (per kg)
2220300003C	Picote Xpress Epoxy Catalyst EU/UK (per kg)
2220300001	Picote Xpress Static Mixing Tip (10 pcs)
<i>Please see the Picote Catalog for the full selection of Coating Brushes and accessories based on your Miller shaft size.</i>	



System includes: Xpress Pump, Hose Reel, Reel Heating Blanket, Small Diameter Hose Package, and 10x flexible static mixing tips.

Picote Xpress Reel Heating Blanket